



Modell		0.35 S 0.35 SN 0.35 SN-AM	0.40 S 0.40 SN 0.40 SN-AM	0.55 S 0.55 SN
Artikel-Nr.		54595.4 54596.2 54597.0	54600.2 54601.0 54602.8	55551.6 55552.4
Tragfähigkeit Capacity	kg	3.500 / 3.500 (SN)*	4.000 / 3.500 (SN)*	5.500 / 3.500 (SN)*
Motorleistung Motor data	kW / A / V	1x 3,6 o. 1 x 5,5 / 20 / 400	1x 3,6 o. 1 x 5,5 / 20 / 400	1 x 5,5 / 20 / 400
Hub- / Senkzeit Lifting- / lowering time	s	3,6 kW - 60 5,5 kW - 35	3,6 kW - 60 5,5 kW - 35	40
A Hubhöhe Lifting height	mm	2.100	2.100	1.780
B Auf- / Überfahrhöhe Drive-on / over height	mm	S - 210 / 260 (AM)** SN* -189 / 239 (AM)**	189 / 239 (AM)**	350
C Fahrbahnbreite Platform width	mm	650	650	710
D Fahrbahnlänge Platform length	mm	4.560	4.800	5.200 + 250 optional
E Aufstellbreite <sup>1</sup> / -länge <sup>2</sup> Set-up width / length	mm	2.260 / 5.530	2.260 / 5.770	2.360 / 5.660
F Fahrbahnbreite SN* Platform width SN*	mm	620	620	710
G Fahrbahnlänge SN* Platform length SN*	mm	1.400 - 1.970	1.400 - 1.970	1.480 - 1.690
H Hubhöhe SN* Lifting height SN*	mm	450	450	450
I Überfahrhöhe SN* Drive over height SN*	mm	50	50	50

SN\* = Radfreiheber / Wheel free scissor

AM\*\* = Achsmess-Set / Wheel alignment set

