



OZZ XR2 P9" Driving light LED - Black

Experience the power of light with OZZ XR2 P9". These 220 mm lights feature a dynamic start-up position light in white and orange. The innovative successor to the original OZZ light series offers a new prominent startup pattern for an impressive visual effect upon ignition. With a boost function, the OZZ XR2 P9" emits 10 600 lumen, providing 1 lux at a distance of 680 meters. The driving beam pattern ensures optimal visibility with a wide and long-range reach. The lights have a color temperature of 5000 K, offering pleasant illumination in all conditions.

Art. no.	88101	Connection	4-pin DT male + female
Pcs LED	16	Cable lenght (mm)	1000 (800+200)
Voltage	10-35V DC	Material bracket	Stainless steel
Theoretical effect	160W	Material housing	Aluminum
Actual effect	R112: 74W, boost: 134W (12V DC), R112: 73W, boost: 130W (24V DC)	Material lens	Polycarbonate
Nominal current	R112: 6,12A, boost: 11,17A (12V DC), R112: 3,04A, boost: 5,42A (24V DC)	Lenght (mm)	220
Functions	High beam, Boost mode, Dynamic position light	Depth (mm)	84,3
Theoretical lumen	15000	Height (mm)	210
Actual lumen	R112: 7010, Boost: 10600	Height including bracket (mm)	227
1 lux @	R112: 480 m, Boost: 680 m	Diameter (mm)	220
Kelvin	5000K	CC (mm)	-
IP-class	IP68/IP69K	Operating temperature	-40°C - +60°C
Beam pattern	Driving	E-mark approval	ECE R148, R149
Position light	Dynamic white and amber	Reference number	50
Color housing	Black	EMC	ECE R10
RAL color	RAL9011	Pcs in master box	4
Color lens	Clear	EAN	7333213101435
Color LED	White, amber	Warranty	3 years

