



## OZZ XR2 P7" Driving light LED - White

Experience the power of light with OZZ XR2 P7". These 178 mm lights feature a dynamic start-up position light in white and orange. The innovative successor to the original OZZ light series offers a new prominent start-up pattern for an impressive visual effect upon ignition. With a boost function, the OZZ XR2 P7" emits 5800 lumen, providing 1 lux at a distance of 470 meters. The driving beam pattern ensures optimal visibility with a wide and long-range reach. The lights have a color temperature of 5000 K, offering pleasant illumination in all conditions.

|                           |                                   |                                      |                 |
|---------------------------|-----------------------------------|--------------------------------------|-----------------|
| <b>Art. no.</b>           | 88104                             | <b>Material bracket</b>              | Stainless steel |
| <b>Pcs LED</b>            | 16                                | <b>Material housing</b>              | Aluminum        |
| <b>Voltage</b>            | 12-35V DC                         | <b>Material lens</b>                 | Polycarbonate   |
| <b>Theoretical effect</b> | 80W                               | <b>Lenght (mm)</b>                   | 178             |
| <b>Actual effect</b>      | 78W (12V DC), 75,6W (24V DC)      | <b>Depth (mm)</b>                    | 72              |
| <b>Nominal current</b>    | 6,5A (12V DC), 3,15A (24V DC)     | <b>Height (mm)</b>                   | 170             |
| <b>Functions</b>          | High beam, Dynamic position light | <b>Height including bracket (mm)</b> | 186             |
| <b>Theoretical lumen</b>  | 7200                              | <b>Diameter (mm)</b>                 | 178             |
| <b>Actual lumen</b>       | 5800                              | <b>CC (mm)</b>                       | -               |
| <b>1 lux @</b>            | 470 m                             | <b>Operating temperature</b>         | -40°C - +60°C   |
| <b>Kelvin</b>             | 5000K                             | <b>E-mark approval</b>               | ECE R148, R149  |
| <b>IP-class</b>           | IP68/IP69K                        | <b>Reference number</b>              | 50              |
| <b>Beam pattern</b>       | Driving                           | <b>EMC</b>                           | ECE R10         |
| <b>Position light</b>     | Dynamic white and amber           | <b>Pcs in master box</b>             | 6               |
| <b>Color housing</b>      | White                             | <b>EAN</b>                           | 7333213101466   |
| <b>RAL color</b>          | RAL9003                           | <b>Warranty</b>                      | 3 years         |
| <b>Color lens</b>         | Clear                             |                                      |                 |
| <b>Color LED</b>          | White, amber                      |                                      |                 |
| <b>Connection</b>         | 4-pin DT male + female            |                                      |                 |
| <b>Cable lenght (mm)</b>  | 1000 (800+200)                    |                                      |                 |

