



OZZ XR3 P9" 65 Arctic Edition Driving light LED

The OZZ XR3 P9" 65 retains the powerful specifications of previous models XR2 P9" and XR3 P9" but also feature a powerful E-approved amber warning light, adding a layer of functionality for professional and safety-conscious drivers. The boost function of this driving light provides an intense 10,424 lumens, achieving 1 lux at up to 735 meters, making it ideal for long-range visibility on dark roads or challenging off-road adventures. It's also equipped with OZZ's signature dual dynamic position light in white and amber. With a color temperature of 5000 K, the XR3 P9" 65 emits a clear, powerful light that enhances visibility even in the darkest of

| | | | |
|----------------------------|--|--------------------------------------|------------------------|
| Art. no. | 88108 | Color LED | White, amber |
| Pcs LED | 16 | Connection | 6-pin DT male + female |
| Voltage | 10-35V DC | Cable lenght (mm) | 1000 (800+200) |
| Theoretical effect | 160W | Material bracket | Stainless steel |
| Actual effect | R112: 74W, boost: 130W (12V DC), R112: 73W, boost: 135W (24V DC) | Material housing | Aluminum |
| Nominal current | R112: 6,14A, boost: 11,17A (12V DC), R112: 3,04A, boost: 5,62A (24V DC) | Material lens | Polycarbonate |
| Functions | High beam, Boost mode, Dynamic position light, Warning light | Lenght (mm) | 220 |
| Theoretical lumen | 15000 | Depth (mm) | 84,3 |
| Actual lumen | R112: 7010, Boost: 10424 | Height (mm) | 210 |
| 1 lux @ | R112: 480 m, Boost: 735 m | Height including bracket (mm) | 227 |
| Kelvin | 5000K | Diameter (mm) | 220 |
| IP-class | IP68/IP69K | CC (mm) | - |
| Beam pattern | Driving | Operating temperature | -40°C - +60°C |
| Flash light pattern | Double flash | E-mark approval | ECE R148, R149, R65 |
| Position light | Dynamic white and amber | Reference number | 50 |
| Color housing | White | EMC | ECE R10 |
| RAL color | RAL9003 | Pcs in master box | 4 |
| Color lens | Clear | EAN | 7350166880170 |
| | | Warranty | 3 years |

