



FEATURES

- ◎ Silicone light strips for internal or external illumination, ideal for transport vehicles and tool carts.
- ◎ From a minimum of 330mm to a maximum of 10,000mm.
- ◎ Options for single-color and dual-color models, with colors including blue, amber, red, cool white, and warm white.
- ◎ Can be directly installed (12V/24V) or with a switch (10-33V).
- ◎ Made from silicone material, suitable for curved surfaces, and resistant to wear and corrosion.
- ◎ Installation options include 3M adhesive or metal brackets.
- ◎ The lampshade features a 3D striped design for even light distribution.



Mode	Length	350mm						500mm						1000mm						2000mm						3000mm						5000mm					
		SINGLE COLOR	Color													○																					
Voltage	12V												24V																								
Max power	5W		8.5W	18W	37W	56W	94W	5W	8.5W	18W	37W	56W	94W	5W	8.5W	18W	37W	56W	94W	5W	8.5W	18W	37W	56W	94W	5W	8.5W	18W	37W	56W	94W						
Lumen	450LM		750LM	1500LM	3000LM	4500LM	7500LM	450LM	750LM	1500LM	3000LM	4500LM	7500LM	450LM	750LM	1500LM	3000LM	4500LM	7500LM	450LM	750LM	1500LM	3000LM	4500LM	7500LM	450LM	750LM	1500LM	3000LM	4500LM	7500LM						

Mode	Length	1050mm				2050mm				1050mm				2050mm			
		DUAL COLOR	Color														
Voltage	12V								24V								
Max power	CW: 7.5W WW: 9.5W A: 7.5W R: 7.5W B: 7.5W				CW: 15W WW: 19W A: 15W R: 15W B: 15W				CW: 7.5W WW: 9.5W A: 7.5W R: 7.5W B: 7.5W				CW: 15W WW: 19W A: 15W R: 15W B: 15W				
Lumen	CW: 550LM WW: 700LM A: 55LM R: 100LM B: 60LM				CW: 1100LM WW: 1400LM A: 110LM R: 200LM B: 120LM				CW: 550LM WW: 700LM A: 55LM R: 100LM B: 60LM				CW: 1100LM WW: 1400LM A: 110LM R: 200LM B: 120LM				

*CW: Cool White, WW: Warm White, A: Amber, R: Red, B: Blue

IP Rating	IP67+69K
Operating Temp	-30°C to +70°C
Dimensions (L*W*H)	X*20*11mm
Certifications	ECE R10
Mounting	3M adhesive surface mounting / Bracket mounting / Screw mounting
Warranty	5 years warranty

GECKO SERIES ITEM SPECIFICATION

1701 — **01** — **TAW**

Configuration
Single-color, DC12V: 01~06
Single-color, DC24V: 07~13
Dual-color, DC12V: 14~15
Dual-color, DC24V: 16~17

LED Color
W
TAW, TBW, TRW, TWW

A: Amber
R: Red
B: Blue
W: White

FDPARTS